

Motori elettrici asincroni trifase 2 poli 230/400V – 400/690V 50Hz

Potenza (kW)	Velocità (gir/min)	In 400V 50Hz (A)	Fattore Potenza (cosφ)	Rendimento (η%)
0.09	2800	0.24	0.77	62
0.12	2800	0.3	0.78	64
0.18	2800	0.5	0.8	66
0.25	2800	0.66	0.81	69
0.37	2800	0.94	0.81	71
0.55	2800	1.33	0.82	74
0.75	2825	1.73	0.83	76
1.1	2825	2.46	0.84	78
1.5	2840	3.26	0.84	79.2
2.2	2840	4.61	0.85	81.5
3	2880	6.01	0.88	83.5
4	2890	7.69	0.88	85.5
5.5	2900	10.5	0.89	86.5
7.5	2900	14.2	0.89	87.1
11	2930	20.2	0.89	88
15	2930	27.4	0.89	89
18.5	2930	32.9	0.9	90
22	2940	38.9	0.9	90.5
30	2950	52.7	0.9	91.2
37	2950	64.5	0.9	92
45	2970	78.2	0.9	92.3
55	2970	95.9	0.9	92.5
75	2970	127.3	0.91	93.2
90	2970	152	0.91	93.8
110	2980	185.3	0.91	94
132	2980	221.4	0.91	94.5
160	2980	265	0.92	94.6
200	2980	330	0.92	94.8
250	2980	411	0.92	95.3
315	2980	517	0.92	95.6